



Accelerator Additive

CHARACTERISTIC

Special additive improving drying time of fillers and clear coats. For the clear coat it can be used only with slow and standard hardener. The drying time will be enhanced by 15%.




NOTE

Not to be used with fast and very fast hardener for clear coat because the drying time will not accelerate, and it may cause defects on the coat, e.g. loss of gloss and adhesion.

RELATED PRODUCTS

XM0004/1	Accelerator Additive	
XC1049/1	Hi-Tech VOC 2K Clear Coat	
XC3016/1	Premium VOC 2K Clear Coat	
XC3016/5	Premium VOC 2K Clear Coat	
XC5014/1	HS Anti Scratch 2K Clear Coat	
XC5014/5	HS Anti Scratch 2K Clear Coat	
XF1091/3.6	Hi-Tech 2K Filler 4:1	
XF3012/1.2	Premium 2K Filler 5:1	
XF3012/3.5	Premium 2K Filler 5:1	



MIXING RATIO FOR FILLERS 4:1		
	Fillers Hardener Accelerator	by volume
		100 25 max 18
MIXING RATIO FOR FILLERS 5:1		
	Fillers Hardener Accelerator	by volume
		100 20 max 20
MIXING RATIO FOR CLEAR COATS 2:1		
	Clear coat Hardener Accelerator	by volume
		100 50 max 8

TECHNICAL DATA					
Product		Packing	Density (20°C)	Colour	Shelf-life
Accelerator	Additive	1L	0,90 g/cm ³	colourless	12 months
XM0004					

**HEALTH AND SAFETY**

Trixxal products are intended only for professional use. They may not be used for any purpose other than that for which they are intended.

When using them, follow the appropriate personal protective equipment, especially respiratory protection, eye and skin protection.

The information referred in data list are based on chemical research and it is on users to use this product in an appropriate manner.

Information on the composition, health and safety, see the Safety Data Sheet, which is available at www.trixxal.com

PRODUCER

ReCorp, s.r.o.
Jána Hollého 699/55
071 01 Michalovce
Slovakia
Telefón: +421 907 319 730
E-mail: info@trixxal.com

