



Hi-Tech Glass putty / Canary yellow

CHARACTERISTIC

Super light putty with glass fibres. It is characterized by creamy consistency, which allows easily to work in 2 - 4 mm layers and to grind with high granulation of abrasives. Possibility of using higher granulation of abrasives (coarse cut P120 - P150). Adequate putty hardness to automotive coatings eliminates creation of crossings between putty and repaired surface. Due to this glass putty can be applied also directly under filling primer. This putty is designed particularly for large repairs of very destroyed surfaces. For filling unevenness on steel, aluminium, galvanized and polyester-glass surfaces. Destined for manual / machine treatment with sanding dry materials, does not fill sandpaper while grinding. Easy to work also on surfaces with complicated shapes even when applying thicker layers. It has a very good surface adhesion, designed for e.g. reinforcing damaged surfaces, increasing the mechanical strength of the repaired element.

APPLICATION

The surface must be cleaned, dry, degreased and matted. Thoroughly mix putty and 2-3% of hardener BPO by weight. Apply within 5 minutes at 20°C. Higher temperature can reduce the pot life and accelerates the drying time.

NOTE

Using too much hardener can lead to topcoat discoloration. It is not recommended to use putty below 15°C.

RELATED PRODUCTS




XP1027/1	Hi-Tech Glass putty / Canary yellow	
----------	-------------------------------------	--

SURFACE PREPARATION



Before coating must be all treated surfaces cleaned, dry, degreased and matted.



MIXING RATIO			
	Hi-Tech Glass putty / Canary yellow XP1027 BPO hardener	by volume	by weight
		100% 2-3%	100g 2-3g
APPLICATION			
	Application process	Apply with spatula	
Process conditions		temperature > 15°C, relative air humidity up to 75%	
Pot life at 20°C		3-5 min	
DRYING TIMES			
		20°C	
	Dry	16-30 min	
	Abrasive	P120 – P320	

TECHNICAL DATA				
Product	Packing	Density (20°C)	Colour	Shelf-life
Hi-Tech Glass putty / Canary yellow XP1027	1L	1,10 g/cm ³	Canary yellow	12 months

VOC INFORMATION
VOC limit: 2004/42/II(b):250 g/l VOC content: <250 g/l

**HEALTH AND SAFETY**

Trixxal products are intended only for professional use. They may not be used for any purpose other than that for which they are intended.

When using them, follow the appropriate personal protective equipment, especially respiratory protection, eye and skin protection.

The information referred in data list are based on chemical research and it is on users to use this product in an appropriate manner.

Information on the composition, health and safety, see the Safety Data Sheet, which is available at www.trixxal.com

PRODUCER

ReCorp, s.r.o.
Jána Hollého 699/55
071 01 Michalovce
Slovakia
Telefón: +421 907 319 730
E-mail: info@trixxal.com

