



SPOT BLENDER

CHARACTERISTIC

Spot blender is ideal for spot repair and blending of 2K clear coats. The Spot blender designed for eliminating of optical differences between new and old applied clear coat.


APPLICATION

Put the Spot blender to the empty spray cup and apply (after spraying 2K Acryl Clear coat) 1-2 thin layers immediately after applying last layer of clear coat.

RELATED PRODUCTS

XM0013/1	Spot Blender	
XC1049/1	Hi-Tech VOC 2K Clear Coat	
XC3016/1	Premium VOC 2K Clear Coat	
XC3016/5	Premium VOC 2K Clear Coat	
XC5014/1	HS Anti Scratch 2K Clear Coat	
XC5014/5	HS Anti Scratch 2K Clear Coat	

SPRAYGUN SETTING

	Spray gun gravity feed	nozzle	pressure
		1,2 – 1,3 mm	as recommended by the manufacturer of the spray gun

**TECHNICAL DATA**

Product	Packing	Density (20°C)	Colour	Shelf-life
Spot Blender XM0013	1L	0,90 g/cm ³	colourless	12 months

HEALTH AND SAFETY

Trixxal products are intended only for professional use. They may not be used for any purpose other than that for which they are intended.

When using them, follow the appropriate personal protective equipment, especially respiratory protection, eye and skin protection.

The information referred in data list are based on chemical research and it is on users to use this product in an appropriate manner.

Information on the composition, health and safety, see the Safety Data Sheet, which is available at www.trixxal.com

PRODUCER

ReCorp, s.r.o.
Jána Hollého 699/55
071 01 Michalovce
Slovakia
Telefón: +421 907 319 730
E-mail: info@trixxal.com

