



## Multi Plus putty / yellow

### CHARACTERISTIC

Multi Plus Putty is multifunctional polyester putty, designed for steel, aluminium, galvanized grounds and polyester laminates. Due to its excellent thixotropy it has very good shaping properties in any required thickness. It can also be used as a finishing putty, leaving smooth surface without pores. For filling unevennesses especially on aluminium and galvanized surfaces. Destined for manual / machine treatment with sanding dry materials. For very large unevennesses putty should be applied in several layers. Does not fill sandpaper while grinding.

### APPLICATION

The surface must be cleaned, dry, degreased and matted. Thoroughly mix putty and 2-3% of hardener BPO by weight. Apply within 5 minutes at 20°C. Higher temperature can reduce the pot life and accelerates the drying time.

### NOTE

Using too much hardener can lead to topcoat discoloration. It is not recommended to use putty below 15°C.

### RELATED PRODUCTS

XP3036/1.8




Multi Plus putty / yellow

### SURFACE PREPARATION



Before coating must be all treated surfaces cleaned, dry, degreased and matted.



MIXING RATIO			
	<b>Multi Plus putty / yellow XP3036 BPO hardener</b>	<b>by volume</b>	<b>by weight</b>
		100% 2-3%	100g 2-3g
APPLICATION			
	<b>Application process</b>	Apply with spatula	
<b>Process conditions</b>		temperature > 15°C, relative air humidity up to 75%	
<b>Pot life at 20°C</b>		3-5 min	
DRYING TIMES			
		<b>20°C</b>	
	<b>Dry</b>	20 min	
	<b>Abrasive</b>	P120 – P320	

TECHNICAL DATA				
Product	Packing	Density (20°C)	Colour	Shelf-life
Multi Plus putty / yellow XP3036	1.8kg	1,84–1,86 g/cm <sup>3</sup>	yellow	12 months

VOC INFORMATION
VOC limit: 2004/42/II(b):250 g/l VOC content: <250 g/l



**HEALTH AND SAFETY**

Trixxal products are intended only for professional use. They may not be used for any purpose other than that for which they are intended.

When using them, follow the appropriate personal protective equipment, especially respiratory protection, eye and skin protection.

The information referred in data list are based on chemical research and it is on users to use this product in an appropriate manner.

Information on the composition, health and safety, see the Safety Data Sheet, which is available at [www.trixxal.com](http://www.trixxal.com)

**PRODUCER**

ReCorp, s.r.o.  
Jána Hollého 699/55  
071 01 Michalovce  
Slovakia  
Telefón: +421 907 319 730  
E-mail: [info@trixxal.com](mailto:info@trixxal.com)

