



## Acrylic thinner

### CHARACTERISTIC

Acrylic Thinner is a mixture of organic solvents for thinning all acrylic fillers and clear coats. It is available in three versions: slow, standard and fast. It allows to use appropriate thinner depending on working temperature and size of repair.

### APPLICATION

Acryl thinner SLOW : it is applied to paint large surfaces, in temperature 25-35°C

Acryl thinner : it is applied to paint large surfaces, in temperature 20-25°C

Acryl thinner FAST : It is usually applied for small repairs. It can be also used by painting larger surfaces if the temperature doesn't exceed 20°C.

### RELATED PRODUCTS

<b>XM0002/1</b>	<b>Acryl thinner</b>	
<b>XM0002/5</b>	<b>Acryl thinner</b>	
<b>XM0015/1</b>	<b>Acryl thinner SLOW</b>	
<b>XM0015/5</b>	<b>Acryl thinner SLOW</b>	
<b>XM0017/1</b>	<b>Acryl thinner FAST</b>	
<b>XM0017/5</b>	<b>Acryl thinner FAST</b>	



TECHNICAL DATA				
Product	Packing	Density (20°C)	Colour	Shelf-life
Acryl thinner XM0002	1L, 5L	0,89-0,90 g/cm <sup>3</sup>	colourless	12 months
Acryl thinner SLOW XM0015	1L, 5L	0,89-0,91 g/cm <sup>3</sup>	colourless	12 months
Acryl thinner FAST XM0017	1L, 5L	0,87-0,89 g/cm <sup>3</sup>	colourless	12 months
HEALTH AND SAFETY				
<p>Trixxal products are intended only for professional use. They may not be used for any purpose other than that for which they are intended.</p> <p>When using them, follow the appropriate personal protective equipment, especially respiratory protection, eye and skin protection.</p> <p>The information referred in data list are based on chemical research and it is on users to use this product in an appropriate manner.</p> <p>Information on the composition, health and safety, see the Safety Data Sheet, which is available at <a href="http://www.trixxal.com">www.trixxal.com</a></p>				
PRODUCER				
ReCorp, s.r.o. Jána Hollého 699/55 071 01 Michalovce Slovakia Telefón: +421 907 319 730 E-mail: <a href="mailto:info@trixxal.com">info@trixxal.com</a>				