



Pigment Paste Black

CHARACTERISTIC

Solvent-borne pigment paste, easy to use for tinting of 1K and 2K acrylic solvent-borne fillers. The paste doesn't influence on application properties of filler.

APPLICATION

Add 1-5 weight % of paste to acrylic filler and mix thoroughly.

The amount of paste is between 1-5% for filler by weight. The amount of used paste is depended on colour of base-coat. For light shade of base-coat the amount of pigment paste should be smaller, for dark shade of base-coat the amount of pigment paste should be higher.

NOTE

Addition of pigment paste can reduce pot life approximately 20 %.

RELATED PRODUCTS

XM0012/1	Pigment Paste Black	
XF1091/3.6	Hi-Tech 2K Filler 4:1	
XF3012/1.2	Premium 2K Filler 5:1	
XF3012/3.5	Premium 2K Filler 5:1	



MIXING RATIO



1 - 5 % by weight for component A (filler)

TECHNICAL DATA

Product	Packing	Density (20°C)	Colour	Shelf-life
Pigment Paste Black XM0012	0.5L	1,10 - 1,13 g/cm ³	black	12 months

HEALTH AND SAFETY

Trixxal products are intended only for professional use. They may not be used for any purpose other than that for which they are intended.

When using them, follow the appropriate personal protective equipment, especially respiratory protection, eye and skin protection.

The information referred in data list are based on chemical research and it is on users to use this product in an appropriate manner.

Information on the composition, health and safety, see the Safety Data Sheet, which is available at www.trixxal.com

PRODUCER

ReCorp, s.r.o.
 Jána Hollého 699/55
 071 01 Michalovce
 Slovakia
 Telefón: +421 907 319 730
 E-mail: info@trixxal.com

