


Technical Data Sheet

<p>General</p> <p>Article number: XA9004xx</p> <p>Description: Colad Aqua Dynamic Masking Tape</p>	
<p>Specification</p> <ul style="list-style-type: none"> - Adhesive type: Rubber solvent based, absolutely free of silicones. - Paper: Saturated water proof green crepe paper. - Thickness: 130 micron (total). 95 micron (backing only). - Weight: 100 g/m² (total). 61 g/m² (backing). 39 g/m² (adhesive). - Elongation: 8%. - Temperature resistance: 130° C - Tensile strength MD: 87,5 N/25 mm. - Adhesion to steel: 4.8 N/25 mm. - Roll lengths: 50 Meter. - Available sizes: Art. No. XA900419: 19 mm. Art. No. XA900425: 25 mm. Art. No. XA900438: 38 mm. Art. No. XA900450: 50 mm. - Packing: Art. No. XA900419: per box of 48 rolls. Art. No. XA900425: per box of 36 rolls. Art. No. XA900438: per box of 24 rolls. Art. No. XA900450: per box of 24 rolls. 	
<p>Remarks</p> <ul style="list-style-type: none"> - Colad Aqua Dynamic Masking Tape is especially designed for the professional car painter and for application in car repair business. - Sharp edge: precise sticking. - Excellent adhesion both to rubber and metal. - Tape can be removed easily and without residue. - The Colad assortment has now 3 types of masking tape, together with the 9020xx and the 9070xx there is a complete line of masking tapes in different price/quality ratio. 	