

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier:** XM0024**Trade name:** TOP GLOSS ADDITIVE**1.2 Relevant identified uses of the substance or mixture and uses advised against** Identified uses: professional use.
Application of the substance / the mixture Thinner, Diluent**1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier:** ReCorp s.r.o.Jána Hollého 699/55
Michalovce 071 01
ICO: 47 503 181
Tel.: +421 907 319 730

Further information obtainable from: info@trixxal.com

1.4 Emergency telephone number:Národné toxikologické a informačné centrum
FNsP Akadémia L. Déjera
Limbová 5, SK – 833 05 Bratislava
+ 421 254 774 166 (24 hours per day)
Fax: + 421 254 774 605**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008



GHS02

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS02



GHS07



GHS08

Signal word Danger**Hazard-determining components of labelling:**

xylene

n-butyl acetate

Hazard statements

H225 Highly flammable liquid and vapour.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 28.07.2015

V- 1

Revision: 02.06.2015

Trade name: TOP GLOSS ADDITIVE

(Contd. of page 1)

H332 Harmful if inhaled.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H304 May be fatal if swallowed and enters airways.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P260 Do not breathe mist/vapours/spray.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Chemical characterisation: Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	25-50%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	25-50%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	5-15%

Additional information: For the wording of the listed risk phrases refer to section 16.**SECTION 4: First aid measures****4.1 Description of first aid measures****General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Immediately remove any clothing soiled by the product.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Take affected persons out of danger area and lay down.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.**After swallowing:** Do not induce vomiting; call for medical help immediately.**4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 28.07.2015

V- 1

Revision: 02.06.2015

Trade name: TOP GLOSS ADDITIVE

(Contd. of page 2)

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media***Suitable extinguishing agents: CO₂, sand, extinguishing powder. Do not use water.**For safety reasons unsuitable extinguishing agents: Water with full jet***5.2 Special hazards arising from the substance or mixture***Can form explosive gas-air mixtures.**Formation of toxic gases is possible during heating or in case of fire.**Carbon monoxide and carbon dioxide***5.3 Advice for firefighters****Protective equipment:***Wear self-contained respiratory protective device.**Do not inhale explosion gases or combustion gases.***Additional information***Cool endangered receptacles with water spray.**Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.**Collect contaminated fire fighting water separately. It must not enter the sewage system.***SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures***Wear protective equipment. Keep unprotected persons away.**Ensure adequate ventilation**Keep away from ignition sources.**Avoid contact with the eyes and skin.***6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.****6.3 Methods and material for containment and cleaning up:***Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).**Dispose contaminated material as waste according to item 13.**Do not flush with water or aqueous cleansing agents***6.4 Reference to other sections***See Section 7 for information on safe handling.**See Section 8 for information on personal protection equipment.**See Section 13 for disposal information.***SECTION 7: Handling and storage****7.1 Precautions for safe handling***Ensure good ventilation/exhaustion at the workplace.**Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).**Do not inhale gases / fumes / aerosols.**Avoid contact with the eyes and skin.**Do not eat, drink, smoke or sniff while working.**Do not allow to enter sewers/ surface or ground water.***Information about fire - and explosion protection:***Keep ignition sources away - Do not smoke.**Protect against electrostatic charges.**Use explosion-proof apparatus / fittings and spark-proof tools.**Fumes can combine with air to form an explosive mixture.***7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:***Store in a cool location.*

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 28.07.2015

V- 1

Revision: 02.06.2015

Trade name: TOP GLOSS ADDITIVE

(Contd. of page 3)

Store only in the original receptacle.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

7.3 Specific end use(s) No further relevant information available.**SECTION 8: Exposure controls/personal protection****Additional information about design of technical facilities:** No further data; see item 7.**8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****1330-20-7 xylene**

WEL (Great Britain)	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
---------------------	--

IOELV (EU)	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin
------------	--

123-86-4 n-butyl acetate

WEL (Great Britain)	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
---------------------	---

67-64-1 acetone

WEL (Great Britain)	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm
IOELV (EU)	Long-term value: 1210 mg/m ³ , 500 ppm

DNELs**1330-20-7 xylene**

Dermal	DNEL	180 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	289 mg/m ³ (acute - systemic effects, workers) 289 mg/m ³ (acute - local effects, workers) 77 mg/m ³ (long-term - systemic effects, workers) 77 mg/m ³ (long-term - local effects, workers)

123-86-4 n-butyl acetate

Dermal	DNEL	7 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	960 mg/m ³ (acute - systemic effects, workers) 960 mg/m ³ (acute - local effects, workers) 480 mg/m ³ (long-term - systemic effects, workers) 480 mg/m ³ (long-term - local effects, workers)

67-64-1 acetone

Dermal	DNEL	186 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	2420 mg/m ³ (acute - local effects, workers) 1210 mg/m ³ (long-term - systemic effects, workers)

PNECs**1330-20-7 xylene**

PNEC	0.327 mg/l (freshwater environment)
------	-------------------------------------

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 28.07.2015

V- 1

Revision: 02.06.2015

Trade name: TOP GLOSS ADDITIVE

(Contd. of page 4)

	12.46 mg/kg (freshwater sediment environment) 2.31 mg/kg (soil) 6.58 mg/l (sewage treatment plants)
123-86-4 n-butyl acetate	
PNEC	0.18 mg/l (freshwater environment) 0.018 mg/l (marine environment) 0.36 mg/l (intermittent releases) 0.981 mg/kg (freshwater sediment environment) 35.6 mg/l (sewage treatment plants)
67-64-1 acetone	
PNEC	10.6 mg/l (freshwater environment) 1.06 mg/l (marine environment) 21 mg/l (intermittent releases) 30.4 mg/kg (freshwater sediment environment) 3.04 mg/kg (marine sediment environment) 29.5 mg/kg (soil) 100 mg/l (sewage treatment plants)
Ingredients with biological limit values:	
1330-20-7 xylene	
BMGV (Great Britain)	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls**Personal protective equipment:****General protective and hygienic measures:**

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Keep ignition sources away - Do not smoke.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A/P2

Use suitable respiratory protective device in case of insufficient ventilation.

Protection of hands:

Protective gloves

Check the permeability prior to each renewed use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation (EN 374).

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 28.07.2015

V- 1

Revision: 02.06.2015

Trade name: TOP GLOSS ADDITIVE

(Contd. of page 5)

Material of gloves

Butyl rubber, BR

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

PVA gloves

Recommended thickness of the material: $\geq 0,7$ mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove materialValue for the permeation: Level 6 ≥ 480 min.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Tightly sealed goggles

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties**General Information****Appearance:**

Form:	Fluid
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Not determined.

pH-value: Not applicable.**Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.

Flash point: < 0 °C**Flammability (solid, gaseous):** Not applicable.**Decomposition temperature:** Not determined.**Auto-ignition temperature:** Not determined.**Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.**Explosion limits:**

Lower:	1.0 Vol %
Upper:	15.0 Vol %

Vapour pressure at 20 °C: 233 hPa

Density at 20 °C:	0.85 g/cm ³
Vapour density	Not determined.
Evaporation rate	Not determined.

Solubility in / Miscibility with water: Not miscible or difficult to mix.**Partition coefficient (n-octanol/water):** Not determined.

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 28.07.2015

V- 1

Revision: 02.06.2015

Trade name: TOP GLOSS ADDITIVE

(Contd. of page 6)

Viscosity:**Dynamic:**

Not determined.

Kinematic:

Not determined.

9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity**10.1 Reactivity** No decomposition if used according to specifications.**10.2 Chemical stability** No decomposition if used and stored according to specifications.**10.3 Possibility of hazardous reactions**

Reacts with alkali, amines and strong acids.

Reacts with oxidising agents.

Fumes can combine with air to form an explosive mixture.

10.4 Conditions to avoid Protect from heat and direct sunlight.**10.5 Incompatible materials:** No further relevant information available.**10.6 Hazardous decomposition products:**

Carbon monoxide and carbon dioxide

Formation of toxic gases is possible during heating or in case of fire.

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity**

Harmful if inhaled.

LD/LC50 values relevant for classification:**1330-20-7 xylene**

Oral	ATE	>2000 mg/kg (-)
Dermal	ATE	1466.67 mg/kg (-)
Inhalative	LC50/4 h	1.5 mg/l (ATE)

123-86-4 n-butyl acetate

Oral	LD50	10760 mg/kg (rat)
Dermal	LD50	10760 mg/kg (rat)
		>14000 mg/kg (rabbit)
Inhalative	LC50/4 h	23.4 mg/l (rat)

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	7400 mg/kg (rabbit)
Inhalative	LC50/4 h	76 mg/l (rat)

Primary irritant effect:**Skin corrosion/irritation**

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)****Germ cell mutagenicity** Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure**

May cause respiratory irritation. May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 28.07.2015

V- 1

Revision: 02.06.2015

Trade name: TOP GLOSS ADDITIVE

(Contd. of page 7)

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information**12.1 Toxicity****Aquatic toxicity:****1330-20-7 xylene**

EC50/24 h	96 mg/l (microorganisms)
EC50/48 h	>1-10 mg/l (<i>Daphnia magna</i>)
IC50/72 h	2.2 mg/l (algae)
LC50/96 h	2.6 mg/l (fish)

123-86-4 n-butyl acetate

EC50/48 h	44 mg/l (<i>daphnia</i>)
EC50/72 h	675 mg/l (algae)
LC50/96 h	18 mg/l (<i>Pimephales promelas</i>)
TT/16 h	115 mg/l (<i>Pseudomonas putida</i>)

67-64-1 acetone

EC50/24 h	(marine sediment environment)
LC50/48 h	8800 mg/l (<i>Daphnia pulex</i>)
LC50/96 h	5540 mg/l (<i>oncorhynchus mykiss</i>)

12.2 Persistence and degradability**1330-20-7 xylene**

Biodegradation	>60 % (readily biodegradable) (OECD 301 F, 28 d, aerobic)
----------------	---

123-86-4 n-butyl acetate

Biodegradation	83 % (readily biodegradable) (OECD 301 D, 28 d, aerobic)
----------------	--

67-64-1 acetone

Biodegradation	90.9 % (readily biodegradable) (OECD 301B, 28d, aerobic)
----------------	--

12.3 Bioaccumulative potential**1330-20-7 xylene**

BCF	25.9 (-)
log Pow	3.15 (-)

123-86-4 n-butyl acetate

BCF	15.3 (-)
log Pow	2.3 (-)

67-64-1 acetone

BCF	3 (-)
log Pow	-0.24 (-)

12.4 Mobility in soil**123-86-4 n-butyl acetate**

log Koc	1.27 (-)
---------	----------

67-64-1 acetone

Kd	1.5 l/kg (-)
----	--------------

Additional ecological information:**General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment**PBT:** Not applicable.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 28.07.2015

V- 1

Revision: 02.06.2015

Trade name: TOP GLOSS ADDITIVE

(Contd. of page 8)

vPvB: Not applicable.**12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

08 01 11* | waste paint and varnish containing organic solvents or other dangerous substances

Uncleaned packaging:**Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information****14.1 UN-Number**

ADR, IMDG, IATA

UN1263

14.2 UN proper shipping name

ADR

1263 PAINT RELATED MATERIAL

IMDG, IATA

PAINT RELATED MATERIAL

14.3 Transport hazard class(es)

ADR, IMDG, IATA



Class

3

Label

3

14.4 Packing group

ADR, IMDG, IATA

II

14.5 Environmental hazards:**Marine pollutant (IMDG):**

No

14.6 Special precautions for user**Danger code (Kemler):**

Warning: Flammable liquids.

33

EMS Number:

F-E,S-E

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

Transport/Additional information:**ADR****Limited quantities (LQ)**

5L

Transport category

2

Tunnel restriction code

D/E

IMDG**Limited quantities (LQ)**

1L

UN "Model Regulation":

UN 1263 PAINT RELATED MATERIAL, 3, II

(Contd. on page 10)

—EN—

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 28.07.2015

V- 1

Revision: 02.06.2015

Trade name: TOP GLOSS ADDITIVE

(Contd. of page 9)

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Directive 2012/18/EU****Named dangerous substances - ANNEX I** None of the ingredients is listed.**Seveso category P5c** FLAMMABLE LIQUIDS**Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t**Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t**National regulations:****Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Sources European Chemicals Agency, <http://echa.europa.eu/>